



One Source. Every Solution. Superior Results.

OSHA'S HAZARD COMMUNICATION STANDARD
U.S. DEPARTMENT OF LABOR
MATERIAL SAFETY DATA SHEET
MSDS

29 CFR 1910.1200
IDENTITY NO: MPCK5000

OMB NO: 1218-0072
NAME: MASTERPIECE FILLER ADHESIVE COLOR KIT

SECTION 1

MANUFACTURER'S/SHIPPER'S NAME: MASTERPIECE INDUSTRIES PRODUCTS
ADDRESS: 6683 SCHUSTER STREET PHONE: (702) 895-9865
CITY: LAS VEGAS STATE: NEVADA CONTACT: KEN WILLIAMS
DATE PREPARED: 4/15/02 EMERGENCY PHONE (CHEMTREC): (800) 424-9300

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Table with 5 columns: HAZARDOUS COMPONENTS, CAS#, OSHA PEL, ACGIH TLV, WEIGHT %. Row 1: UNSATURATE POLYESTER RESIN, N/A, NOT ESTABLISHED, NOT ESTABLISHED, 25-75%

NOTE: SOME COLOR PASTES MAY CONTAIN ONE OR ALL OF THE FOLLOWING MATERIALS

Table with 5 columns: Component Name, CAS#, OSHA PEL, ACGIH TLV, WEIGHT %. Rows include XYLENE, ETHYL BENZENE, and TOLUENE with their respective hazard values.

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

PHYSICAL STATE: LIQUID EVAPORATION RATE: SLOWER THAN N-BUTYL ACETATE
SPECIFIC GRAVITY: 1.1 - 2.3 VOC CONTENT: <32 G/L

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE CLASS: IIIB AUTO IGNITION: UNKNOWN
FLASH POINT: >93.3° C (>200° F) UEL: UNKNOWN
LEL: UNKNOWN

Table with 5 columns: NFPA HAZARD RATING, H, F, R, S. Row 1: (0=LEAST, 4=EXTREME), 1, 1, 1, 0

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID: HEAT AND DIRECT SUNLIGHT, ELEVATED TEMPERATURES AND SOURCE OF IGNITION.
INCOMPATIBLE MATERIALS TO AVOID: STRONG ALKALIES AND OXIDIZING AGENTS. WILL REACT EXOTHERMICALLY WITH ISOCYANATES.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: THERMAL DECOMPOSITION OR COMBUSTION CAN PRODUCE FUMES CONTAINING CARBON MONOXIDE/DIOXIDE, ALDEHYDES, CARBON, AND OTHER TOXIC GASES.
HAZARDOUS POLYMERIZATION: NO

SECTION 6 - HEALTH HAZARD DATA

MPCK5000 Page 2

INGESTION: SWALLOWING IN LARGE AMOUNTS MAY BE HARMFUL. MAY GET INTO LUNGS DURING INGESTION OR VOMITING WHICH COULD RESULT IN LUNG INFLAMMATION OR INJURY. MAY CAUSE GASTROINTESTINAL DISTURBANCES, PAIN AND DISCOMFORT.

SKIN: MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY DRY THE SKIN AND LEAD TO DERMATITIS. SYMPTOMS MAY INCLUDE REDNESS, BURNING, AND STINGING.

INHALATION: INHALING SMALL AMOUNTS OF VAPOR AND MIST IS POSSIBLE AND DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS. BREATHING LARGE AMOUNTS OF VAPOR OR MIST MAY BE HARMFUL, USUALLY IN HIGH CONCENTRATIONS.

EYE: MAY CAUSE IRRITATION. LIQUID SPLASHES MAY RESULT IN MORE SERIOUS INJURIES. MAY CAUSE LACHRYMATION (TEARS), REDNESS, AND STINGING.

EMERGENCY FIRST AID PROCEDURES:

INGESTION: DO NOT INDUCE VOMITING (ASPIRATION HAZARD). SEEK IMMEDIATE MEDICAL AID.

SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. CONSULT A PHYSICIAN IF ANY SIGNS OR SYMPTOMS DESCRIBED IN THIS DOCUMENT OCCUR. WASH CONTAMINATED CLOTHING.

INHALATION: REMOVE VICTIM FROM EXPOSURE. IF VICTIM IS UNCONSCIOUS, ADMINISTER ARTIFICIAL RESPIRATION AND/OR OXYGEN AS NEEDED. SEEK MEDICAL AID.

EYES: FLUSH WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. SEEK IMMEDIATE MEDICAL AID.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

PROCEDURE FOR CLEANUP: REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE IN A CLOSED CONTAINER. IF LARGE SPILL, DIKE THE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATER SYSTEMS OR SEWERS. DISPOSE OF HAZARDOUS WASTE ONLY IN A CERTIFIED FACILITY FOR HAZARDOUS WASTE HANDLING IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. CALL CHEMTREC EMERGENCY PHONE NUMBER (24 HOUR): 800-424-9300

HANDLING AND STORAGE: READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL. REFER TO PRODUCT LABEL OR MANUFACTURERS TECHNICAL BULLETINS FOR THE PROPER USE AND HANDLING OF THIS MATERIAL. DO NOT USE OR STORE NEAR FLAME, SPARKS OR HOT SURFACES. USE ONLY IN WELL VENTILATED AREA. KEEP CONTAINER CLOSED. DO NOT WELD, HEAT OR DRILL CONTAINER. EMPTIED CONTAINER MAY STILL CONTAIN HAZARDOUS OR EXPLOSIVE VAPOR OR LIQUID. DO NOT STORE IN TEMPERATURES GREATER THAN 140° F.

SECTION 8 - CONTROL MEASURES

ENGINEERING CONTROLS: USE ADEQUATE VENTILATION TO KEEP THE AIRBORNE CONCENTRATIONS OF THIS MATERIAL BELOW THE RECOMMENDED EXPOSURE STANDARD.

RESPIRATORY PROTECTION: IF A TLV OR PEL LISTED IN THIS DATA SHEET IS EXCEEDED, THEN SUITABLE RESPIRATORY PROTECTION MUST BE WORN TO PREVENT OVEREXPOSURE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN LIMITED CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS. PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED.

PROTECTIVE CLOTHING: WEAR APPROPRIATE CLOTHING AND IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT.

EYE PROTECTION: WEAR SAFETY GLASSES, FACE SHIELD OR CHEMICAL GOGGLES.

OTHER USE PRECAUTIONS: EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE FOR USE IN EMERGENCY SITUATIONS.