

Instructions for Hardrock Special Formula Marble Polish FP6005

EQUIPMENT NEEDED:

1. Floor buffing Machine 175 RPM, 16" to 22" diameter, total weight of 130 to 140 pounds.
2. **Hardrock Marble Polish**.
3. Spray bottle with adjustable spray nozzle.
4. **Hardrock Steel Wool Pads**.
5. Small hand-size steel wool pads.
6. For first application only: **Hardrock Mable Stripper**.
7. For maintenance: **Hardrock No Rinse Neutral Marble Cleaner**.

THE FIRST APPLICATION:

CLEANING THE FLOOR:

1. **Important!!!** Before applying the first treatment of **Hardrock Marble Polish**, the floor must be completely cleaned to remove all traces of dirt, wax and sealer.
2. Strip the floor with **Hardrock Marble Stripper**.
3. If the floor has visible grout between the tiles, use a stiff brush or scraper to clean the grout.
4. After stripping, rinse the floor twice with clean water and a clean mop. Allow the floor to dry completely.
5. Clean the machine to remove stripper.

POLISHING THE FLOOR:

1. Shake the large container of **Hardrock Marble Polish** and fill the spray bottle. Adjust nozzle to a slight stream spray. Shake often during use.
2. Place a clean **Hardrock Steel Wool Pad** under the floor buffer. As pad becomes wet and loaded with polish, turn it over or change pads.
3. Apply polish in a 3' x 3' section of the floor. Spray 3 or 4 squirts of **Hardrock Polish** onto the floor, then buff with a side-to-side motion until dry. Move to an adjacent area and repeat. Rotate in four sections until desired shine appears. Then move on to four new sections.
4. For the first application, at least three treatments will be needed to obtain desired shine. The best results have been obtained when floor has a good shine, and feels slightly sticky when walked on.
Caution! Do not over buff. Buffing dry may cause floor to be slippery.
5. After polishing, buff the corners by hand with a small steel wool pad to remove residue and even out the shine. Then sweep with a clean dry dust mop to remove polish residue and shavings.

MAINTENANCE:

1. Sweep the floor daily to remove dirt, dust or other grit. Spills should be cleaned up as soon as possible with clean water.
2. Damp mop floor daily or as often as possible with **Hardrock No Rinse Neutral Marble Cleaner**.
3. **Hardrock Marble Polish** should be applied on a regular schedule to preserve the shine. Polish with floor buffer and clean steel wool pads. If used on a regular basis, one treatment should restore the shine.
4. You need not do the entire floor during each maintenance. Traffic areas may be touched up to restore even shine.
5. After maintenance, finish up as in step five above.

SAMPLE TESTING: Before using, always test each surface to be treated in a small inconspicuous area to insure the desired results will be achieved. Consult supplier for further information and precautions, including Material Safety Data Sheets.

WARNING: Contains Magnesium Silicofluoride. Avoid contact with eyes or skin use only with rubber gloves wear dust mask

First Aid:

Skin: Wash with soap and water, especially between nails.

Eyes: Flush with water for 15 minutes.

Ingestion: Drink large amounts of water. Follow with mineral oil or egg whites.

Inhalation: Get person to fresh air. If unconscious call physician.

Page 1



One Source. Every Solution. Superior Results.

Container Disposal:

Rinse three times with water. Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill (dump), or by incineration, or if allowed by State and local authorities, by burning. If burned, stay away from smoke.

Keep out of reach of children.

For sale to, use and storage by service persons only.